



HP Sales Central

HP LaserJet Enterprise MFP M725dn (CF066A)

Active as of 5/1/2013

Detailed Specifications

Accessories

HP LaserJet 500-sheet Feeder and Tray CF239A, HP LaserJet 1 x 500-sheet Paper Feeder with Cabinet and Stand CF243A, HP LaserJet 3 x 500-sheet Feeder and Stand CF242A, HP LaserJet 3500-sheet HCI Feeder and Stand CF245A, HP Staple Cartridge Refill C8091A, HP 200-pin DDR2 512 MB x64 DIMM CF306A, HP LaserJet MFP Analog Fax Accessory 500 CC487A, HP LaserJet 110V Maintenance/Fuser Kit CF249A, HP LaserJet 220V Maintenance/Fuser Kit CF254A, HP 100 ADF Roller Replacement Kit L2718A

Acoustic power emissions (active copy)

7.1 B(A)

Acoustic power emissions (active scan)

6.8 B(A)

Acoustic power emissions (active, printing)

6.8 B(A)

Acoustic power emissions (ready)

5.0 B(A)

Acoustic power footnote number

[5]

Acoustic power note

Acoustic values are subject to change. For current information see hp.com/support. Configuration tested: base model, simplex printing, A4 paper at an average of 40 ppm.

Acoustic pressure emissions bystander (active copy)

56 dB(A)

Acoustic pressure emissions bystander (active scan)

52 dB(A)

Acoustic pressure emissions bystander (active, printing)

54 dB(A)

Acoustic pressure emissions bystander (ready)

36 dB(A)

Additional information about HP in the countries

hp.com

ADF Capacity

100

Automatic document feeder capacity

Standard, 100 sheets

Automatic paper sensor

No

Bit depth

24-bit

Bottom margin (A4)

2 mm

Cable included

No, please purchase USB cable separately

Capacity

500 GB

Code name

Everest

Color scanning

Yes

Compatible Operating Systems

Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008 (32 and 64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2012 (64-bit); Mac OS X 10.6, OS X Lion, OS X Mountain Lion; For the latest operating system support see: Citrix and Windows Terminal Services (<http://www.hp.com/go/upd>); Novell (<http://www.novell.com/iprint>); Linux (<http://www.hplip.net>); UNIX (<http://www.hp.com/go/unix>, <http://www.hp.com/go/unixmodelscripts>, http://www.hp.com/go/jetdirectunix_software); SAP device types (<http://www.hp.com/go/sap/drivers>, <http://www.hp.com/go/sap/print>); HP ePrint Mobile Driver (<http://www.hp.com/go/eprintmobiledriver>)

Connectivity, optional

HP Jetdirect ew2500 802.11b/g Wireless Print Server J8021A; HP Jetdirect 2700w USB Wireless Print Server J8026A

Connectivity, standard

2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host

Control panel

8.0-in (20.3 cm) color LCD with touchscreen; rotating (adjustable angle) display; illuminated Home button (for quick return to the Home menu); Easy Access USB; Hardware Integration Pocket

Copier scaling (ADF)

25 to 400%

Copier settings

Sides; Collate; Paper Selection; Reduce/Enlarge; Image Adjustment; Content Orientation; Pages per sheet; Booklet format; Edge to Edge; Optimize Text/Picture; Original Size; Job Build

Copier smart software features

Auto scale; Reduce/Enlarge from scanner glass (25 to 400%); Collate; Auto color detection; Two-sided copying; Image adjustments (darkness, background cleanup, sharpness); Job build; staple

Copies, maximum

Up to 9999 copies

Copy reduce / enlarge settings

25 to 400%

Copy resolution (black graphics)

600 x 600 dpi

Copy resolution (black text)

600 x 600 dpi

Copy speed (black, normal quality, A4)

Up to 41 cpm

Copy speed black (normal, letter)

Up to 40 cpm

Copy speed black duplex (A4)

Up to 27 ipm

Copy speed black duplex (Letter)

Up to 27 ipm

Copy speed footnote number

[4]

Copy speed note

First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Count of cartons per pallet layer

1

Count of layers in pallet

1

Country of origin

Made in China; Netherlands; Mexico

Datasheet photo 1

Publication photos/M725dn.jpg

Datasheet photo 4

Publication photos/C2LF96Awalkaround.jpg

Digital sending optional features

Optional via HP Digital Sending Software (HP DSS); Send to folder; Send-to-workflow; Send-to-printer; Authentication; Digital fax (send to LAN, Internet); OCR; Local Address Book

Digital sending standard features

Scan to e-mail; Save-to-Network Folder; Save-to-USB drive; Send to FTP; Send to LAN Fax; Send to Internet Fax; Local Address Book; SMTP over SSL

Display

8.0-in (20.3 cm) touchscreen; LCD (color graphics) ; rotating (adjustable angle) display; illuminated Home button (for quick return to the Home menu)

Downloadable software

Universal Print Driver for Windows, Windows CD image, Mac CD Image, Web JetAdmin, Smart Web Printing In-House Marketing, Unix/Linux driver, Enterprise installer utility, Plug and Play bundles

Driver updates

Recent printer drivers for all supported operating systems are available at hp.com/go/ljMFPM725_software

Duplex ADF scanning

Yes, reversing ADF

Duplex printing

Automatic (standard)

Duty cycle (monthly, A4)

Up to 200,000 pages

Duty cycle (monthly, letter)

Up to 200,000 pages

Duty cycle footnote number

[9]

Duty cycle note

Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Eco label

ENERGY STAR® qualified

Electromagnetic compatibility

CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:1998+A1 +A2; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries

Energy efficiency

ENERGY STAR® qualified, CECP, EPEAT® Silver

Energy savings feature technology

HP Auto-On/Auto-Off Technology; Instant-on Technology

Energy star certified

Yes

Envelope Feeder

No

Environmental

Mercury Free

Fax Transmission Speed Footnote Number

[6]

Faxing

Optional

FCC Class A emissions

FCC Class A emissions - for use in commercial environments, not residential environments

File Format Supported

Digital Send: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A; Scan to easy access USB: PDF, JPEG, TIFF, MTIFF, XPS, PDF/A; Print from easy access USB: PDF, PS, Print Ready files (.prn, .pcl, .cht)

Finished output handling

Sheetfed

First copy out black (letter)

As fast as 10.5 sec

First page out black (A4, ready)

As fast as 10 sec

First page out black (letter, ready)

As fast as 10 sec

First page out color (letter, sleep)

As fast as 20.5 sec

First page out footnote

Exact speed varies depending on the system configuration, software application, driver and document complexity.

First page out footnote number

[8]

Fonts and typefaces

105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts

Functions

Print, copy, scan

HP ePrint capability

Yes

Image legal disclaimer

Product image may differ from actual product

Input capacity

Up to 600 sheets

Internal Storage

Standard, embedded HP High-Performance Secure Hard Disk, minimum 500 GB; AES 256 hardware encryption or greater; Secure erase capabilities (Secure File Erase-Temporary Job Files, Secure Erase-Job Data, Secure ATA Erase-Disk)

Left margin (A4)

2 mm

Legal disclaimer

© Copyright 2015 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

Levels of grayscale

256

Mac compatible

Yes

Maximum dimensions (W x D x H)

34.1 x 38.9 x 24 in

Maximum dimensions (W x D x H)

865 x 989 x 609 mm

Maximum Input Capacity (envelopes)

Up to 10 envelopes

Maximum input capacity (sheets)

Up to 4600 sheets

Maximum Memory

1.5 GB

Maximum metric depth

989

Maximum metric height

609

Maximum metric width

865

Maximum output capacity (sheets)

Up to 250 sheets

Maximum print area

308 x 465.9 mm

Media size (ADF)

Letter; letter-R; executive; legal; 11 x 17 in; U.S. checks; 4 x 6 in; 5 x 7 in; 5 x 8 in; A3; A4; A4-R; A5; A6; B4 (JIS); B5 (JIS); B6 (JIS); 16K

Media size, tray 1

A4; A5; B4 (JIS); B5 (JIS); 76.2 x 127 to 312 x 469.9 mm

Media size, tray 2

A4; A5; B4 (JIS); B5 (JIS); 148 x 210 to 297 x 363 mm

Media size, tray 3

A3; A4; A5; B4 (JIS); B5 (JIS); 148 x 210 to 297 x 431 mm

Media sizes supported

A3; A4; A5; B4 (JIS); B5 (JIS)

Media sizes supported

Tray 1, 2: Letter, legal, executive, 8.5 x 13 in; Tray 3: letter, legal, executive, 8.5 x 13 in, 11 x 17 in

Media sizes supported, key

A4; A3

Media sizes supported, key

Letter; Legal; 11 x 17 in

Media sizes, custom

Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to 11.7 x 14.3 in; Tray 3: 5.8 x 8.3 to 11.7 x 17 in

Media sizes, custom

Tray 1: 76.2 x 127 to 312 x 469.9 mm; Tray 2: 148 x 210 to 297 x 363 mm; Tray 3: 148 x 210 to 297 x 431 mm

Media type and capacity, ADF

Sheets: 100

Media type and capacity, tray 1

Sheets: 100; envelopes: 10; labels: 100; transparencies: 100; postcards: 10

Media type and capacity, tray 2

Sheets: 250

Media type and capacity, tray 3

Sheets: 250

Media types

Paper (color, letterhead, light, plain, preprinted, prepunched, recycled, rough, tough paper), bond, cardstock, envelope, labels, transparency, vellum

Media weight (tray 1)

60 to 199 g/m²

Media weight (tray 2)

60 to 120 g/m²

Media weight (tray 3)

60 to 120 g/m²

Media weight, supported

Tray 1: 16 to 53 lb; Tray 2, 3: 16 to 32 lb

Media weight, supported

Tray 1: 60 to 199 g/m²; Trays 2, 3: 60 to 120 g/m²

Media weights, supported ADF

12 to 53 lb

Media weights, supported ADF

45 to 199 g/m²

Memory

1 GB

Memory Slots

1 slot, 200-pin, DDR2 DIMM

Memory upgrade

Expandable to 1.5 GB through 512 MB industry-standard DIMM

Metric depth

649

Metric height

609

Metric width

614

Minimum dimensions (W x D x H)

24.2 x 25.6 x 24 in

Minimum dimensions (W x D x H)

614 x 649 x 609 mm

Minimum System Requirements

Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 (64-bit); 200 MB available hard disk space; operating system compatible hardware system requirements, see <http://www.microsoft.com>

Minimum System Requirements for Macintosh

Mac OS X 10.6, OS X Lion, OS X Mountain Lion; 1 GB available hard disk space; operating system compatible hardware system requirements, CD-ROM/DVD-ROM or Internet, see apple.com

Mobile printing capability

HP ePrint; Apple AirPrint™; Mopria™-certified

Multitasking supported

Yes

Network capabilities

Yes, via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional)

Network protocols, supported

IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, XMPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print

Network ready

Standard (built-in Gigabit Ethernet)

Non-Operating Humidity Range

10 to 90% RH

Number of print cartridges

1 (black)

Number of users

10-30 Users

Operating humidity range

20 to 80% RH

Operating system (supported note)

Windows Installer has the same Operating System support as the driver except the following: Windows XP SP2+ (32-bit only); Windows Server 2003 SP1+ (32-bit only); Windows Vista Starter not supported in Driver nor Installer

Operating system supported footnote number

[12]

Operating temperature range

10 to 32.5°C

Operating temperature range

50 to 91°F

Output capacity

Up to 250 sheets

Package dimensions (W x D x H)

29.9 x 29.3 x 32.8 in

Package dimensions (W x D x H)

760 x 745 x 832 mm

Package weight

151 lb

Package weight

68.6 kg

Page yield footnote

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.

Page yield footnote number

[3]

Pallet dimensions

29.9 x 29.3 x 32.8 in

Pallet dimensions (W x D x H)

760 x 745 x 832 mm

Pallet weight

151 lb

Pallet weight

68.6 kg

Paper handling input, optional

Optional 500-sheet input tray, optional 1 x 500-sheet paper feeder with cabinet and stand, optional 3 x 500-sheet paper feeder with stand, optional 3500-sheet high capacity input tray with stand

Paper handling input, standard

100-sheet multipurpose tray, two 250-sheet input trays

Paper handling output, standard

250-sheet output bin

Paper trays, maximum

6

Paper trays, standard

3

Ports

2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host

Power

110-volt input voltage: (Option #BGJ, #201) 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input

voltage: (Option #AAZ) 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier)

Power consumption

890 watts (Active print/copy), 39 watts (Ready), 6.5 watts (Sleep), 0.3 watts (Off)

Power consumption footnote number

[1]

Power consumption Note

Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages; this will damage the printer and void the product warranty. Values subject to change, see

hp.com/support for current information.

Power supply type

Built-in power supply

Print colors

No

Print languages

HP PCL 6, HP PCL 5, HP postscript level 3 emulation, PDF 1.4

Print quality black (best)

Up to 1200 x 1200 dpi

Print quality black (normal)

HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi with HP Resolution Enhancement technology

Print Resolution Technologies

HP ProRes 1200 (1200 x 1200 dpi), HP FastRes 1200 (1200 dpi quality), HP Resolution Enhancement technology 600 dpi, 300 dpi

Print speed

Print speed up to 40 ppm (black)

Print speed (A4/letter) footnote number

[7]

Print speed black (ISO, A4)

Up to 41 ppm

Print speed black (ISO, letter)

Up to 40 ppm

Print speed black (normal, A3)

Up to 20 ppm

Print speed black (normal, tabloid)

Up to 20 ppm

Print speed duplex (A4)

Up to 28 ipm

Print speed duplex (letter)

Up to 28 ipm

Print speed footnote

Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Print technology

Laser

Print Technology

Laser

Printer Management

HP Web Jetadmin, HP Utility (Mac)

Printer smart software features

HP ePrint, Apple AirPrint, Mopria-certified, Open Extensibility Platform, FutureSmart Firmware, HP Auto-On/Auto-Off technology, Easy Access USB, Image Preview

Processor speed

800 MHz

Product note

FCC Class A emissions device for use in commercial environments, not residential environments[13]

Quantity per pallet

1

Recommended media weight (duplex)

16 to 32 lb

Recommended media weight (duplex)

60 to 199 g/m²

Recommended monthly page volume

5000 to 20,000

Recommended monthly scan volume

6250 to 10,500

Recommended operating humidity range

30 to 70% RH

Recommended operating temperature range

10 to 32.5°C

Recommended operating temperature range

50 to 91°F

Replacement cartridges

HP 14A Black LJ Toner Cartridge CF214A (10,000 pages); HP 14X Black LJ Toner Cartridge CF214X (17,500 pages)

Replacement cartridges footnote

Average declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies.

Replacement cartridges footnote number

[2]

Resolution

600 dpi

Right margin (A4)

2 mm

RMN number

BOISB-1105-01

Safety

IEC 60950-1:2005 +A1; EN60950-1: 2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/LED Product); UL/cUL Listed (USA/Canada); GS Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2010; Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries

Scan file format

PDF, JPEG, TIFF, MTIFF, XPS, PDF/A

Scan input modes

Copy, scan to e-mail, scan to network folder, scan to USB, save to device memory, fax, Open Extensibility Platform (OXF) applications

Scan resolution, hardware

Up to 600 x 600 dpi

Scan resolution, optical

Up to 600 dpi

Scan size (ADF), maximum

11 x 17 in

Scan size (ADF), maximum

297 x 420 mm

Scan size (ADF), minimum

2.7 x 5.8 in

Scan size (ADF), minimum

68 x 148 mm

Scan size, maximum

11 x 17 in

Scan size, maximum

297 x 420 mm

Scan speed (normal, A4)

Up to 50 ppm (black and white), up to 30 ppm (color)

Scan speed (normal, letter)

Up to 49 ppm (black and white), up to 30 ppm (color)

Scan speed duplex (normal, A4)

Up to 20 ipm (black and white), up to 15 ipm (color)

Scan speed duplex (normal, letter)

Up to 19 ipm (black and white), up to 14 ipm (color)

Scan speed footnote

Actual speeds may vary depending on scan resolution, network conditions, computer performance and application software.

Scan speed footnote number

[11]

Scan technology

Charge Coupled Device (CCD)

Scanner advanced features

Optimize text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect color; Edge erase; Auto tone; Auto job notification; Blank page suppression; HP Quick Sets

Scanner type

Flatbed, ADF

Security management

Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in

Services

Onsite replacement of your printer's maintenance kit including parts, materials, and labor

Services

Onsite service the next business day after the service call is received

Services

Onsite support within four hours after a service call received within the coverage window

Services (Care Pack)

HP 3y Nbd + DMR LsrJt M725 MFP Supp U7A14E (Recommended); HP 3y 4h 9x5 LJ M725 MFP HW Support U7A08E; HP 3y 4h 13x5 LJ M725 MFP HW Support U7A09E; HP 2y PW Nbd LJ M725 MFP HW Support U7Y73PE; HP 1y PW Nbd + DMR LJ M725 MFP Supp U7Y76PE; HP Network Install high-end LaserJet Multifunction printer Service U2014E

Services description headline 01

4 hr Onsite Support:

Services description headline 02

Next Business Day Onsite Support:

Services description headline 03

Maintenance Kit Replacement Service:

Software included

Windows Installer, HP PCL 6 discrete driver, Mac SW Link to Web, [Postscript emulation driver & Installer on Web], Note: No Mac SW inbox

Standard media sizes (duplex)

60 to 120 g/m²

Standard media sizes (duplex, imperial)

16 to 32 lb

Standard output capacity (envelopes)

Up to 50 envelopes

Standard output capacity (transparencies)

Up to 250 sheets

Storage device and direct print support

Front-facing USB/Flash drive

Storage temperature range

0 to 60°C

Storage temperature range

32 to 140°F

Sub-brand name

LaserJet

SureSupply footnote number

[10]

SureSupply note

HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. For more information, visit hp.com/go/SureSupply; only available with Original HP supplies; Internet access required.

SureSupply supported

Yes

Target user and print volume

For teams over 25 users; Prints up to 20,000 pages/month

Tariff numbers

8443321010; 8443318000

Tech spec footnote

[1]Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages; this will damage the printer and void the product warranty. Values subject to change, see hp.com/support for current information.

Tech spec footnote

[10]HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. For more information, visit hp.com/go/SureSupply; only available with Original HP supplies; Internet access required.

Tech spec footnote

[11]Actual speeds may vary depending on scan resolution, network conditions, computer performance and application software.

Tech spec footnote

[12]Windows Installer has the same Operating System support as the driver except the following: Windows XP SP2+ (32-bit only); Windows Server 2003 SP1+ (32-bit only); Windows Vista Starter not supported in Driver nor Installer

Tech spec footnote

[2]Average declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies.

Tech spec footnote

[3]Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.

Tech spec footnote

[4]First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[5]Acoustic values are subject to change. For current information see hp.com/support. Configuration tested: base model, simplex printing, A4 paper at an average of 40 ppm.

Tech spec footnote

[6]Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory.

Tech spec footnote

[7] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[8] Exact speed varies depending on the system configuration, software application, driver and document complexity.

Tech spec footnote

[9] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Technology logo, print 1

Publication logos/AMS_EnergyStar.jpg

Technology logo, print 2

Publication logos/AMS_Compatible with Win7.jpg

Technology logo, print 3

Publication logos/AMS_mac_hires.jpg

Technology logo, print 4

Publication logos/AMS_hp_eprint.jpg

Technology logo, print 5

Publication logos/AMS_USB easy access.jpg

Technology logo, print 6

Publication logos/AMS_Epeat bronze.jpg

Top key features

100-sheet ADF; Front-facing USB printing; Scan to email/PDF; Two-sided printing

Top margin (A4)

2 mm

Tray capacity

600

Typical electricity consumption (TEC) number

2.8 kWh/Week (Blue Angel); 0.653 kWh/Week (Energy Star 3.0)

UNSPSC code

43212110

UPC number

(201) 887111647597; (AB1) 887111016751; (AB2) 887111016768; (ABJ) 887111016775; (ABT) 887111016812; (ABY) 887111016829; (ACJ) 887111016782; (ACQ) 887111016836; (B13) 888182819586; (B19) 887111016843; (BAZ) 887111016850; (BBU) 887111016799; (BGJ) 887111016867; (BGM) 887111016805

Warranty

One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to <http://www.hp.com/support> to learn about HP award winning service and support options in your region.

Waste electrical and electronic weight

56.6 kg

Weight

119.3 lb

Weight

54.11 kg

What's in the box

HP LaserJet Enterprise MFP M725; HP Black LaserJet Toner Cartridge (10,000 pages); Hardware Installation Guide; Support flyer; Warranty guide; Printer documentation and software on CD-ROM; Power cord

Wireless capability

Optional, enabled with purchase of a hardware accessory

© Copyright 2013 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.