HP LaserJet Pro 500 color MFP M570dn (CZ271A)

Active as of 11/1/2012

Detailed Specifications

Accessories

HP Color LaserJet 500-sheet Paper and Heavy Media Tray CF084A, HP LaserJet Printer Cabinet CF085A, HP Color LaserJet CE254A Toner Collection Unit CE254A, 110-volt Fuser Kit CE484A, 220-volt Fuser Kit CE506A

Acoustic power emissions (active copy)

6.7 B(A)

Acoustic power emissions (active, printing)

6.6 B(A)

Acoustic power emissions (ready)

4.7 B(A)

Acoustic power footnote number

[7]

Acoustic power note

Values are subject to change. For current information see Product Support page at hp.com/support. Configuration tested for printing: simplex, mono and simplex, color. Configuration tested for copying: duplex, color.

Acoustic pressure emissions bystander (active copy)

53 dB(A)

Acoustic pressure emissions bystander (active, printing)

52 dB(A)

Acoustic pressure emissions bystander (ready)

33 dB(A)

Additional information about HP in the countries

hp.com

Auto fax reduction supported

Yes

Automatic document feeder capacity

Standard, 50 sheets

Automatic paper sensor

No

Bit depth

24-bit (8-bit for color duplex jobs)

Bottom copy margin

4.2 mm

Bottom margin (A4)

5 mm

Cable included

No, please purchase USB cable separately

Code name

Epic

Color scanning

Yes

Compatible Operating Systems

Full software installs supported on: Windows 10 (32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Windows 7 (32-bit and 64-bit), Windows Vista (32-bit and 64-bit), Windows XP (32-bit) (SP2 or higher), and Windows Server 2012; Driver only installs supported on: Windows Server 2008 (32-bit and 64-bit), Windows Server 2008 R2, Windows Server 2003 (32-bit) (SP3 or higher); Mac OS X v 10.6, OS X Lion (10.7) & OS X Mountain Lion (10.8); Linpus Linux (9.4, 9.5), Red Hat Enterprise Linux 5.0 (supported with a pre-built package), SuSE Linux (10.3, 11.0, 11, 11.1, 11.2), Fedora (9, 9.0, 10, 10.0, 11.0, 11, 12, 12.0), Ubuntu (8.04, 8.04.1, 8.04.2, 8.10, 9.04, 9.10, 10.04), Debian (5.0, 5.0.1, 5.0.2, 5.0.3) (supported by the automatic installer); HPUX 11 and Solaris 8/9

Connectivity, standard

1 Hi-Speed USB 2.0; 1 Host USB; 1 Gigabit 10/100/1000T Ethernet; 1 RJ -11 (Fax); 1 RJ-11 (Phone only)

Control panel

3.5-in intuitive touchscreen control panel with color graphic display; Buttons (Home, Cancel, Help, Right/Left Arrows, Back); LED indicator lights (Ready, Error, Wireless)

Copier scaling (ADF)

25 to 400%

Copier settings

Number of copies; Reduce/Enlarge; Ligher/Darker; Optimize; Paper; Multi-page copy; Collation; Tray select; Two-sided; Draft mode; Image adjustment; Set as new defaults; Restore defaults

Copies, maximum

Up to 99 copies

Copy margin left

4.2 mm

Copy margin right

4.2 mm

Copy margin top

4.2 mm

Copy reduce / enlarge settings

25 to 400%

Copy resolution (black graphics)

Up to 300 x 300 dpi

Copy resolution (black text)

Up to 300 x 300 dpi

Copy resolution (color text and graphics)

Up to 300 x 300 dpi

Copy speed (black, normal quality, A4)

Up to 30 cpm

Copy speed (color, normal quality, A4)

Up to 30 cpm

Copy speed black (normal, letter)

Up to 31 cpm

Copy speed color (normal, letter)

Up to 31 cpm

Copy speed footnote number

[6]

Copy speed note

First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration and document.

Count of cartons per pallet layer

1 (EMEA); 2 (AMS, APJ)

Count of layers in pallet

1 (EMEA); 3 (AMS, APJ)

Country of origin

Made in China

Datasheet photo 1

Publication photos/M570dn.jpg

Digital sending standard features

Scan-to-E-mail with LDAP e-mail address lookup

Dimension note (imperial)

Without trays and covers extended

Dimension(W x D x H) Footnote Number

[1]

Display

3.5" (8.89 cm) touchscreen, LCD (color graphics)

Distinctive ring detection supported

Yes

Downloadable software

Windows Full Software Solution; HP Universal Print Drivers; HP PrintView; HP EcoPrint Console; HP ePrint Mobile Driver; Mac Software Solution; Linux Software Solution; Unix Print Driver

Driver updates

Latest supported operating systems and print drivers available at hp.com/go/support

Duplex ADF scanning

Yes, dual head duplexing, color scan

Duplex printing

Automatic (standard)

Duty cycle (monthly, A4)

Up to 75,000 pages

Duty cycle (monthly, letter)

Up to 75,000 pages

Duty cycle footnote number

[11]

Duty cycle note

Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Electromagnetic compatibility

CISPR 22: 2008/EN 55022: 2010 Class A, EN 61000-3-2: 2006+A1:2009+A2:2009, EN 61000-3-3:2008, EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part 15 Class A (USA), ICES-003, Issue 4, (Canada), GB9254-2008, GB17625.1-2003, EMC Directive 2004/108/EC with CE Marking (Europe), other EMC approvals as required by individual countries

Energy efficiency

CECP; EPEAT® Silver

Energy savings feature technology

HP Auto-On/Auto-Off Technology; Instant-on Technology; Instant-on Copy

Energy star certified

No

Envelope Feeder

No

Fax Auto Redial

Yes

Fax Broadcast Locations

120

Fax delayed sending

Yes

Fax forwarding

Yes

Fax memory

Up to 250 pages

Fax memory

Up to 250 pages

Fax PC Interface Supported

Yes, PC fax send only

Fax phone TAM interface supported

Yes

Fax Polling

Yes (receive only)

Fax Remote Retrieval

No

Fax resolution black

203 x 196 dpi

Fax Resolution Black (best)

Up to 300 x 300 dpi

Fax smart software features

Permanent fax memory backup, auto fax reduction, auto redialing, delayed sending, fax forwarding, TAM interface, polling, junk barrier, distinctive ring detection, cover page wizard, block fax, billing codes, save and load, poll receive, fax activity reports, dial prefix setting, print fax log

Fax Speed Dials, Maximum Number

Up to 120 numbers

Fax telephone mode supported

Yes

Fax Transmission Speed

33.6 kbps

Fax transmission speed (letter)

3 sec per page

Fax Transmission Speed Footnote Number

[8]

Fax Transmission Speed Note

Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory.

Faxing

Yes

FCC Class A emissions

FCC Class A emissions - for use in commercial environments, not residential environments

Finished output handling

Sheetfed

First copy out black (letter)

As fast as 10 sec

First copy out color (letter)

As fast as 14 sec

First page out black (A4, ready)

As fast as 10.5 sec

First page out black (letter, ready)

As fast as 10.5 sec

First page out color (A4, ready)

As fast as 10.5 sec

First page out color (letter, ready)

As fast as 10.5 sec

First page out color (letter, sleep)

As fast as 15 sec

First page out footnote

Exact speed varies depending on the system configuration, software application, driver and document complexity.

First page out footnote number

[10]

Fonts and typefaces

84 scalable TrueType fonts

Functions

Print, copy, scan, fax

HP ePrint capability

Yes

Image legal disclaimer

Product image may differ from actual product

Input capacity

Up to 350 sheets

Junk fax barrier

Yes

Left margin (A4)

5 mm

Legal disclaimer

© Copyright 2015 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

Levels of grayscale

256

Mac compatible

Yes

Maximum dimensions (W x D x H)

825 x 915 x 948 mm

Maximum Input Capacity (envelopes)

Up to 10 envelopes

Maximum input capacity (sheets)

Up to 850 sheets

Maximum Memory

256 MB

Maximum output capacity (sheets)

Up to 250 sheets

Maximum print area

210.9 x 350.6 mm

Media size (ADF)

Letter; legal; executive; A4; A5; B5 (JIS); statement; 4 x 6; custom sizes 127 x 127 to 216 x 356 mm

Media size, tray 1

A4; A5; A6; B5 (JIS); B6 (JIS); 16K; 10 x 15 cm; postcards (JIS single, JIS double); envelopes (ISO DL, ISO C5, ISO B5)

Media size, tray 2

A4; A5; B5 (JIS); 16K

Media size, tray 3

A4; A5; B5 (JIS); 16K

Media sizes supported

Tray 1: A4; A5; A6; B5 (JIS); B6 (JIS); 16K; 10 x 15 cm; postcards (JIS single, JIS double); envelopes (ISO DL, ISO

Media sizes supported

Tray 1: Letter, legal, executive, 8.5×13 in, 4×6 in, 5×8 in, envelopes (No 10, Monarch); Tray 2: letter, executive; Optional tray 3: letter, legal, executive, 8.5×13 in; Automatic two-sided printing unit: letter, legal, executive, 8.5×13 in

Media sizes supported, key

10 x 15 cm; A4; Envelopes

Media sizes supported, key

4 x 6 in; Letter; Legal; Envelopes

Media sizes, custom

Tray 1: 3×5 in to 8.5×14 in; Tray 2: 5.8×8.3 in to 8.5×11.7 in; Optional Tray 3: 5.8×8.3 in to 8.5×14 in; Automatic two-sided printing unit: 5.8×8.3 in to 8.5×14 in

Media sizes, custom

Tray 1: 76×127 to 216×356 mm; Tray 2: 148×210 to 216×297 mm; Optional 500-sheet tray 3: 148×210 to 216×356 mm; Automatic two-sided printing unit: 148×210 to 216×356 mm

Media type and capacity, ADF

Sheets: 50

Media type and capacity, tray 1

Sheets (75 g/m²): 100; labels, transparencies, cardstock (163 g/m²): 50; cardstock (216 g/m²): 30; envelopes: 10

Media type and capacity, tray 2

Sheets (75 g/m²): 250; cardstock (163 g/m²), labels, transparencies: 100

Media type and capacity, tray 3

Sheets (75 g/m²): 500; cardstock (163 g/m²), labels, transparencies: 200 (optional tray)

Media types

Paper (bond, brochure, colored, glossy, letterhead, photo, plain, preprinted, prepunched, recycled, rough), postcards, transparencies, labels, envelopes

Media weight (tray 1)

60 to 216 g/m² (plain paper), 105 to 220 g/m² (glossy paper)

Media weight (tray 2)

60 to 163 g/m² (plain paper), 105 to 220 g/m² (glossy paper)

Media weight (tray 3)

60 to 176 g/m² (plain paper), 105 to 220 g/m² (glossy paper) (optional 500-sheet tray)

Media weight, supported

Tray 1: 16 to 58 lb (plain paper); 28 to 58 lb (glossy paper); Tray 2: 16 to 43 lb (plain paper); 28 to 58 lb (glossy paper); Optional Tray 3: 16 to 47 lb (plain paper); 28 to 58 lb (glossy paper)

Media weight, supported

Tray 1: 60 to 216 g/m² (plain paper), 105 to 220 g/m² (glossy paper); Tray 2: 60 to 163 g/m² (plain paper), 105 to 220 g/m² (glossy paper); Optional Tray 3: 60 to 176 g/m² (plain paper), 105 to 220 g/m² (glossy paper); Automatic two-sided printing unit: 60 to 163 g/m² (plain paper), 105 to 220 g/m² (glossy paper)

Media weights, supported ADF

60 to 90 g/m²

Memory

256 MB

Memory upgrade

Not expandable

Minimum dimensions (W x D x H)

515 x 500 x 538 mm

Minimum System Requirements

Windows 8, Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit): 1 GHz 32-bit (x86) or 64-bit (x64) processor, 1 GB RAM (32-bit) or 2 GB RAM (64-bit), 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port; Windows XP (32-bit) SP2: Pentium® 233 MHz processor, 512 MB RAM 400 MB free hard disk space, CD/DVD-ROM or Internet, USB or Network port

Minimum System Requirements for Macintosh

Mobile printing capability

HP ePrint; Apple AirPrint™; Mopria™-certified

Modem

33.6 kbps

Multitasking supported

Yes

Native scan file format

PDF, JPG

Network capabilities

Yes, via built-in Gigabit 10/100/1000T Ethernet

Network protocols, supported

Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP Print, FTP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless); Security: SSL Security and certificate management, 802.1x

Network ready

Standard (built-in Gigabit 10/100/1000T Ethernet)

Non-Operating Humidity Range

10 to 90% RH

Number of print cartridges

4 (1 each black, cyan, magenta, yellow)

Number of users

5-15 Users

Operating humidity range

10 to 70% RH

Operating system (supported note)

For Windows Server 2003 32-bit and 2008 32-bit and 64-bit only the printer driver and scanner driver are installed.

Operating system supported footnote number

[16]

Operating temperature range

10 to 30°C

Operating temperature range

50 to 81ºF

Output capacity

Up to 250 sheets

Package dimensions (W x D x H)

733 x 644 x 730 mm

Package weight

101.2 lb

Package weight

45.9 kg

Page yield footnote

Declared yield value in accordance with ISO/IEC 19798 in continuous printing. Actual yields vary considerably based on images printed and other factors. For more information visit: hp.com/go/learnaboutsupplies

Page yield footnote number

[5]

Pallet dimensions (W x D x H)

756 x 680 x 869 mm (EMEA); 1325 x 756 x 2190 mm (AMS, APJ)

Pallet weight

276.4 kg

Pallet weight

Paper handling input, optional

Optional 500-sheet paper tray 3

Paper handling input, standard

100-sheet multipurpose tray, 250-sheet input tray 2, 50-sheet automatic document feeder

Paper handling output, standard

250-sheet face-down output bin

Paper trays, maximum

3

Paper trays, standard

2

Ports

1 Hi-Speed USB 2.0; 1 Host USB; 1 Gigabit 10/100/1000T Ethernet; 2 RJ-11

Power

Input voltage 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 12 A

Power consumption

605 watts (Printing), 440 watts (Copying), 52 watts (Ready), 8.1 watts (Sleep), 0.3 watts (Off)

Power consumption footnote number

[3]

Power consumption Note

Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

Power supply type

Internal (Built-in) power supply

Print colors

Yes

Print languages

HP PCL 6, HP PCL 5, HP postscript level 3 emulation, PDF (v 1.7), AirPrint™ compatible

Print quality black (best)

Up to 600 x 600 dpi

Print quality black (normal)

Up to 600 x 600 dpi

Print quality color (best)

Up to 600 x 600 dpi

Print Resolution Technologies

HP ImageREt 3600

Print speed

Print speed up to 31 ppm (black) and 31 ppm (color)

Print speed (A4/letter) footnote number

[9]

Print speed black (ISO, A4)

Up to 30 ppm

Print speed black (ISO, letter)

Up to 31 ppm

Print Speed Color (ISO)

Up to 30 ppm

Print speed color (ISO)

Up to 31 ppm

Print speed duplex (A4)

Up to 27 ipm

Print speed duplex (letter)

Up to 29 ipm

Print speed footnote

Simplex speed measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. Duplex speed measured internally and may be less than 29 ipm depending on how print job is configured. See h41302.www4.hp.com/km/saw/view.do?docId=emr_na-c03735617&hsid=49244267&sz=5785 for details.

Print technology

Laser

Print Technology

Laser

Printer Management

Windows: HP Device Toolbox, Status Alerts (default install), SNP Alerts (minimum network install), HP Web Jetadmin (download); Mac: HP Utility

Printer smart software features

HP ePrint, Apple AirPrint™, Mopria-certified, HP Auto-On/Auto-Off technology, Simplified control panel, Compact design, Clear and Sharp Chinese and India fonts (China and India only)

Processor speed

800 MHz

Product note

FCC Class A emissions device for use in commercial environments, not residential environments[12]

Quantity per pallet

1 (EMEA); 6 (AMS, APJ)

Recommended media weight (duplex)

16 to 43 lb

Recommended media weight (duplex)

60 to 163 g/m²

Recommended monthly page volume

1500 to 4000

Recommended monthly page volume footnote number

[12]

Recommended monthly page volume note

HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Recommended operating humidity range

20 to 60% RH

Recommended operating temperature range

15 to 27ºC

Recommended operating temperature range

59 to 80.6ºF

Replacement cartridges

HP 507A Black LaserJet Toner Cartridge (yield ~5500 pages) CE400A; HP 507X Black LaserJet Toner Cartridge (yield ~11,000 pages) CE400X; HP 507A Cyan LaserJet Toner Cartridge (yield ~6000 pages) CE401A; HP 507A Yellow LaserJet Toner Cartridge (yield ~6000 pages) CE402A; HP 507A Magenta LaserJet Toner Cartridge (yield ~6000 pages) CE403A

Replacement cartridges footnote

Note: ships with preinstalled standard toner cartridges (yield ~5500 black, ~6000 cyan, magenta, and yellow pages)

Replacement cartridges footnote number

[4]

Resolution

Up to 300 x 300 dpi (color and mono, ADF); Up to 1200 x 1200 dpi (mono, flatbed)

Resolution (black and white, standard mode)

203 x 98 dpi

Resolution (black and white, superfine mode)

300 x 300 dpi (no halftone)

Resolution (black photo grayscale)

300 x 300 dpi

Right margin (A4)

5 mm

RMN number

BOISB-1200-00

Safety

IEC 60950-1+A1 (International), EN 60950-1+A11 +A1+A12 (EU), IEC 60825-1, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1 (Class 1 Laser/LED Device), Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries

Scan file format footnote

HP Scan software included in the box - file formats supported through software running on a PC

Scan file format footnote number

[15]

Scan input modes

From PC: Solution Center Lite (Windows Vista®, Windows® XP) or Device Stage (Windows® 7); TWAIN-compliant or WIA-compliant software

Scan resolution, hardware

Up to 300 x 300 dpi (color and mono, ADF); Up to 1200 x 1200 dpi (mono, flatbed)

Scan resolution, optical

Up to 300 x 300 dpi (color and mono, ADF); Up to 1200 x 1200 dpi (mono, flatbed)

Scan size (ADF), maximum

216 x 356 mm

Scan size (ADF), maximum

8.5 x 14 in

Scan size (ADF), minimum

127 x 177 mm

Scan size (ADF), minimum

5 x 7 in

Scan size. maximum

216 x 297 mm

Scan size, maximum

8.5 x 11.7 in

Scan size, minimum

Any size smaller than A4

Scan size, minimum

Any size smaller than A4

Scan speed (normal, A4)

Up to 19.5 ppm (b&w), up to 14 ppm (color)

Scan speed (normal, letter)

Up to 20.5 ppm (b&w), up to 15 ppm (color)

Scan speed duplex (normal, A4)

Up to 35.5 ipm (b&w), up to 13.5 ipm (color)

Scan speed duplex (normal, letter)

Up to 36 ipm (b&w), up to 13.5 ipm (color)

Scan speed footnote

Scan speed measured from ADF with default settings (save to PDF). Exact speed varies depending on the system configuration and document complexity.

Scan speed footnote number

[14]

Scan technology

Scanner advanced features

Scan-to-E-mail; Scan-to-network folder (stand alone solution); Scan to Cloud; Scan to USB

Scanner type

Flatbed, ADF

Security management

Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 community password change, SNMPv3, 802.1x, Firewall, Access Control List; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication, SASL authentication

Software included

Windows: HP Installer/Uninstaller, HP PCL 6 print driver, HP WIA Scan Driver, HP TWAIN Scan Driver, HP Scan, HP Fax Setup Wizard, HP Send Fax, HP Fax Print Driver, Status Alerts, HP Update, DXP; Mac: HP Installer/Uninstaller, HP Postscript driver, HP Scan, HP Setup Assistant, HP Fax Print Driver, HP Utility, HP Firmware Updater

Software scan file format

Windows: JPG, BMP, PDF, TIFF, PNG, RTF; Mac: JPG, TIFF, PNG, PDF, Searchable PDF, RTF, TXT

Standard media sizes (duplex)

A4; A5; B5 (JIS)

Standard media sizes (duplex, imperial)

Letter; legal; executive; 8.5 x 13 in

Standard output capacity (envelopes)

Up to 10 envelopes

Standard output capacity (transparencies)

Up to 100 sheets

Storage device and direct print support

Storage devices not supported

Storage temperature range

0 to 35°C

Storage temperature range

32 to 95ºF

SureSupply footnote number

[13]

SureSupply note

HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. For more information, visit hp.com/go/SureSupply; only available with Original HP supplies; Internet access required.

SureSupply supported

Yes

Target user and print volume

For teams up to 15 users; Prints up to 4,000 pages/month

Tariff numbers

8443310000 (AM); 8443318000 (EU)

Tech spec footnote

[1] Without trays and covers extended

Tech spec footnote

[10]Exact speed varies depending on the system configuration, software application, driver and document complexity.

Tech spec footnote

[11]Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Tech spec footnote

[12]HP recommends that the number of pages per month of imaged output be within the stated range for

optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Tech spec footnote

[13]HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. For more information, visit hp.com/go/SureSupply; only available with Original HP supplies; Internet access required.

Tech spec footnote

[14]Scan speed measured from ADF with default settings (save to PDF). Exact speed varies depending on the system configuration and document complexity.

Tech spec footnote

[15]HP Scan software included in the box - file formats supported through software running on a PC

Tech spec footnote

[2] With toner cartridges

Tech spec footnote

[3] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

Tech spec footnote

[4]Note: ships with preinstalled standard toner cartridges (yield ~5500 black, ~6000 cyan, magenta, and yellow pages)

Tech spec footnote

[5]Declared yield value in accordance with ISO/IEC 19798 in continuous printing. Actual yields vary considerably based on images printed and other factors. For more information visit: hp.com/go/learnaboutsupplies

Tech spec footnote

[6] First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration and document.

Tech spec footnote

[7] Values are subject to change. For current information see Product Support page at hp.com/support. Configuration tested for printing: simplex, mono and simplex, color. Configuration tested for copying: duplex, color.

Tech spec footnote

[8]Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory.

Tech spec footnote

[9]Simplex speed measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. Duplex speed measured internally and may be less than 29 ipm depending on how print job is configured. See h41302.www4.hp.com/km/saw/view.do?docId=emr_na-c03735617&hsid=49244267&sz=5785 for details.

Technology logo, print 1

Publication logos/AMS_EnergyStar.jpg

Technology logo, print 2

Publication logos/AMS_Compatible with Win7.jpg

Technology logo, print 3

Publication logos/AMS_hp_eprint.jpg

Technology logo, print 4

Publication logos/AMS_USB_hi speed.jpg

Technology logo, print 5

Publication logos/AMS_mac_hires.jpg

Technology logo, print 6

Publication logos/AMS_AirPrint.jpg

Telecom compliance (fax capability)

Fax Telecom: ES 203 021; FCC Part 68; Industry Canada CS03; NOM-151-SCTI-1999 (Mexico); other Telecom approvals as required by individual countries

Telephone handset supported

No

Top key features

50-sheet ADF; Scan to email/PDF; Two-sided printing

Top margin (A4)

5 mm

Twain version

Version 1.9

Typical electricity consumption (TEC) number

3.259 kWh/Week

UNSPSC code

43212110

UPC number

(201) 886112935283; (696) 886112935252; (ABO) 886112935146; (AB1) 886112935153; (AB2) 886112935160; (ABJ) 887111302854; (ABT) 886112935207; (AC4) 887111012555; (AC8) 886112935269; (ACJ) 886112935177; (ACQ) 886112935221; (AKV) 886112935276; (B13) 888182820094; (B19) 886112935238; (BAZ) 886112935245; (BBU) 886112935184; (BGJ) 886112935290; (BGM) 886112935191

Warranty

One-year, on-site limited warranty

Web address for additional information

http://www.hp.com/go/eprintcenter

Weight

40.8 kg

Weight (imperial) footnote number

[2]

Weight note (imperial)

With toner cartridges

What's in the box

HP LaserJet Pro 500 color MFP M570dn; HP Black LaserJet Toner Cartridge (~5500 pages), Cyan, Magenta, and Yellow Toner Cartridges (~6000 pages); Printer documentation and software on CD-ROM; Installation quide; Support flyer; Warranty card; Power cord

Wireless capability

No

© Copyright 2012 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.