



HP Sales Central

HP Color LaserJet Enterprise M751n (T3U43A)

Active as of 5/1/2019

Detailed Specifications

Accessories

HP LaserJet 550-sheet Paper Tray T3V27A, HP LaserJet Stand T3V28A, HP LaserJet 2x550-sheet Paper Tray and Stand T3V29A, HP LaserJet 2700-sheet HCI Paper Tray and Stand T3V30A, HP High-Performance Secure Hard Disk (FIPS Drive) B5L29A, HP Internal USB Ports B5L28A, HP Foreign Interface Harness B5L31A, HP 1GB DDR3x32 144-Pin 800MHz SODIMM E5K48A Accy, HP 2 GB DDR3x32 144-Pin 800MHz SODIMM Accy E5K49A, HP SmartCard NIPRNet Solution for US Government CC543B, HP SmartCard SIPRNet Solution for US Government F8B30A, HP Jetdirect 2900nw Print Server J8031A, HP Jetdirect 3100w BLE/NFC/Wireless Accy 3JN69A, HP USB Universal Card Reader X3D03A, HP HIP2 Keystroke Reader Y7C05A, HP Legic Reader 4QL32A, HP FIPS-140-2 Secure Hard Disk Drive 5EL03A, TAA compliant DIMM 2NR09A, HP Accessibility Assistant 2MU47A

Acoustic power emissions (active, printing)

6.6 B(A)

Acoustic power emissions (ready)

4.5 B(A)

Acoustic power footnote number

[7]

Acoustic pressure emissions bystander (active, printing)

51 dB(A)

Acoustic pressure emissions bystander (ready)

30 dB(A)

Automatic paper sensor

Yes

Best technical electricity consumption (TEC) footnote number

[5]

Blue Angel compliant

No, please refer to the ECI (Ecolabel Comparison Information) document

Bottom margin (A4)

5 mm

Cable included

No, please purchase USB cable separately

Code name

Banff

Compatible Network Operating Systems

Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit, Failover Cluster 2008 R2, Failover Cluster 2012 R2, Terminal server 2008 R2, Remote Desktop server 2012 R2, Citrix Server 6.5, Citrix XenApp & XenDesktop 7.6, Novell iPrint server, Citrix Ready Kit Certification - Up to Citrix Server 7.18 for more information see <http://citrixready.citrix.com>, Linux- For more information see <http://developers.hp.com/hp-linux-imaging-and-printing>, Unix- For more information see <http://hp.com/go/unixmodelscripts>, UPD PCL6 / PS Printer Drivers, Supported for Compatible Network Operating systems please see <http://hp.com/go/upd>

Compatible Operating Systems

Windows Client OS (32/64 bit), Windows 10, Windows 8.1, Windows 8 Basic, Windows 8 Pro, Windows 8 Enterprise, Windows 8 Enterprise N, Windows 7 Starter Edition SP1, UPD Windows 7 Ultimate, Mobile OS, iOS, Android, Mac, Apple® macOS Sierra v10.12, Apple® macOS High Sierra v10.13, Apple® macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to

<http://support.hp.com>, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) - User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported operating systems see www.hp.com/go/upd

Connectivity, optional

HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A, (Dual band Wireless Station and Wi-Fi Direct functionality); HP Jetdirect 2900nw Print Server J8031A (Dual band Wireless Station)

Connectivity, standard

1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 rear host ports; 1 walkup USB 2.0 host port; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network port; 1 Hardware Integration Pocket 2nd generation (HIP2)

Control panel

2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad

Count of cartons per pallet layer

1

Count of layers in pallet

4

Country of origin

Made in Japan

Datasheet photo 1

Publication photos/T3U43A.jpg

Datasheet photo 4

Publication photos/M751 Series Walkaround.jpg

Dimension note (imperial)

Without paper trays extended

Dimension(W x D x H) Footnote Number

[2]

Dimensions (W x D x H) Note

Without paper trays extended

Display

2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad

Display area (imperial)

2.7 in

Display area (metric)

6.86 cm

Downloadable software

From <http://123.hp.com>, HP Easy Start (Guided Software Install for Windows and Mac); From <http://hp.com> for Windows OS, Full-solution software and drivers, Basic-solution software and drivers, HP PCL6 XPS Discrete Print Driver, Product Documentation and Support; From <http://hp.com> for Mac OS, HP Easy Start (Guided Software Install), HP Mac PS Print Driver, HP Easy Admin; For Mobile OS, iOS For more information see <http://hp.com/go/businessmobileprinting>, Android For more information see <http://hp.com/go/businessmobileprinting>; From <http://hp.com> for printer administrators, Printer Administrator Resource Kit (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator), HP Universal Print Drivers PCL6 GDI & PS GDI for Windows, HP ePrint Software (Mobile Driver for Windows), SAP Print Drivers for more information see <http://support.hp.com/us-en/document/c05051702>, HP Web JetAdmin, HP JetAdvantage Security Manager, HP Roam, HPLIP Linux Printer Driver for more information see <http://hplipopensource.com/hplip-web/index.html>, Unix Model Script Printer Driver for more information see <http://hp.com/go/unixmodelscripts>, ReadIris

Driver updates

Current HP printer drivers and software can be obtained from the HP Customer Care Web site: In the US, go to <http://www.hp.com/support/colorljm751>; Outside the US, go to <http://www.hp.com/support> 1 Select the country/region 2 Select Software and Drivers 3 Select Printer 4 Enter a product name/number 5 The operating system is automatically detected 6 Select a driver or other software 7 Then select DOWNLOAD

Duplex printing

Manual (driver support provided)

Duty cycle (monthly, A4)

Up to 150,000 pages

Duty cycle (monthly, letter)

Up to 150,000 pages

Duty cycle footnote number

[9]

Duty cycle note

Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Electromagnetic compatibility

CISPR 22:2008 (International) - Class A, CISPR32:2012 (International) - Class A, EN 55032: 2012 (EU) - Class A, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010, EMC Directive 2014/30/EU, FCC CFR 47 Part 15 Class A/ICES-003, Issue 6 Class A. Other EMC approvals as required by individual countries.

Energy savings feature technology

HP Auto-On/Auto-Off Technology; Instant-on Technology

Energy star certified

No

Envelope Feeder

No

Environmental

Mercury free

FCC Class A emissions

FCC Class A emissions - for use in commercial environments, not residential environments

Finished output handling

Sheetfed

First page out black (A4, ready)

As fast as 5.7 sec

First page out black (A4, sleep)

As fast as 11.5 sec

First page out black (letter, ready)

As fast as 5.7 sec

First page out black (letter, sleep)

As fast as 11.5 sec

First page out color (A4, ready)

As fast as 6.1 sec

First page out color (A4, sleep)

As fast as 11.5 sec

First page out color (letter, ready)

As fast as 6.1 sec

First page out color (letter, sleep)

As fast as 11.5 sec

First page out footnote number

[14]

Fonts and typefaces

105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts

Functions

Print

Image legal disclaimer

Product image may differ from actual product

Input capacity

Up to 650 sheets (80 g/m² paper)

Internal Storage

Optional 500 GB HDD: HP Secure High Performance Hard Disk drive 500 GB B5L29A; HP FIPS-140-2 Secure Hard Disk Drive 5EL03A

Left margin (A4)

5 mm

Mac compatible

Yes

Maximum dimensions (W x D x H)

1051 x 992 x 443 mm

Maximum dimensions (W x D x H)

41.4 x 39.1 x 17.4 in

Maximum input capacity (sheets)

Up to 4450 sheets (80 g/m² paper)

Maximum Memory

3.5 GB

Maximum metric depth

992

Maximum metric height

443

Maximum metric width

1051

Maximum output capacity (sheets)

Up to 250 sheets

Maximum print area

310 x 447 mm

Media size, tray 1

A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL

Media size, tray 2

A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS)

Media size, tray 3

Optional 1x550 and 2x550 tray and stand: A3, A4, A4-R, A5, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 2700-sheet HCl paper tray and stand: A4

Media sizes supported

100-sheet multipurpose Tray 1: A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL; 550-sheet input Tray 2: A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 1x550 and 2x550 tray and stand: A3, A4, A4-R, A5, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 2700-sheet HCl paper tray and stand: A4 100-sheet multipurpose Tray 1: A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL; 550-sheet input Tray 2: A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 1x550 and 2x550 tray and stand: A3, A4, A4-R, A5, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS); Oficio 216x340, 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS); Optional 2700-sheet HCl paper tray and stand: A4

Media sizes supported

100-sheet multipurpose Tray 1: Statement, 3 x 5 index card, 4 x 6 index card, 5 x 7 index card, 5 x 8 index card, Letter, Letter-R, Legal, Executive, 11 x 17 in; 8.5 x 13, 12 x 18, Envelopes: #9, #10, Monarch; 550-sheet input Tray 2: Letter, Letter-R, Legal, Executive, 8.5 x 13, 11 x 17 in; Optional 1x550 and 2x550 tray and stand: Letter, Letter-R, Legal, Executive, 8.5 x 13, 11 x 17 in, 12 x 18; Optional 2700-sheet HCl paper

tray and stand: Letter

Media sizes supported, key

10 x 15 cm; A4; A3; Envelopes

Media sizes supported, key

4 x 6 in; Letter; Legal; 11 x 17 in; Envelopes

Media sizes, custom

100-sheet multipurpose Tray 1: 2.5 x 5 to 12.6 x 18 in; 550-sheet input Tray 2: 5.8 x 5.8 to 11.7 x 17 in; Optional 1x550 and 2x550 tray and stand: 5.8 x 5.8 to 12.6 x 18 in; Optional 2700-sheet HCl paper tray and stand: 11 x 8.27 to 11.7 x 8.5 in

Media sizes, custom

100-sheet multipurpose Tray 1: 64 x 127 to 320 x 457.2 mm; 550-sheet input Tray 2: 148 x 148 to 297 x 431.8 mm; Optional 1x550 and 2x550 tray and stand: 148 x 148 to 320 x 457.2 mm; Optional 2700-sheet HCl paper tray and stand: 279.4 x 210 mm to 297 x 215.9

Media type and capacity, tray 1

Sheets: 100 (80 g/m²); Transparencies: 50; Envelopes: 10; Labels: 50

Media type and capacity, tray 2

Sheets: 550 (80 g/m²); Transparencies: 200; Labels: 200

Media type and capacity, tray 3

Sheets: 550 (80 g/m²); Transparencies: 200; Labels: 200

Media types

Paper (plain, heavy, extra heavy, glossy, light, recycle, tough), envelopes, labels, glossy film, cardstock, transparencies

Media weight (tray 1)

60 to 300 g/m² plain papers, up to 220 g/m² glossy/coated

Media weight (tray 2)

60 to 256 g/m² plain papers, up to 220 g/m² glossy/coated

Media weight (tray 3)

60 to 256 g/m² plain papers, up to 220 g/m² glossy/coated

Media weight, supported

100-sheet multipurpose Tray 1: 16 to 80 lb, 550-sheet input Tray 2: 16 to 68 lb, Optional 1x550 and 2x550 tray and stand: 16 to 68 lb, Optional 2700-sheet HCl paper tray and stand: 16 to 68 lb

Media weight, supported

100-sheet multipurpose Tray 1: 60 to 300 g/m², 550-sheet input Tray 2: 60 to 256 g/m², Optional 1x550 and 2x550 tray and stand: 60 to 256 g/m², Optional 2700-sheet HCl paper tray and stand: 60 to 256 g/m²

Memory

1.5 GB

Memory card compatibility

Not available

Memory Slots

1 slot, 144-pin DDR3 x32 SODIMM

Memory upgrade

Expandable to 3.5 GB through 1 GB 144-pin DDR3 x32 SODIMM

Metric depth

589

Metric height

399

Metric width

556

Minimum dimensions (W x D x H)

21.9 x 23.2 x 15.7 in

Minimum dimensions (W x D x H)

556 x 589 x 399 mm

Minimum System Requirements

2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see [microsoft.com](https://www.microsoft.com);

Minimum System Requirements for Macintosh

2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see [apple.com](https://www.apple.com);

Mobile printing capability

HP ePrint; Apple AirPrint™; Mopria™ Certified; Google Cloud Print™; HP Roam

Network capabilities

Yes, via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional)

Network protocols, supported

IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print

Number of print cartridges

4 toner cartridges (1 each for black, cyan, magenta, yellow)

Number of users

5-20 Users

Operating humidity range

10 to 80% RH

Operating system supported footnote number

[11]

Operating temperature range

10 to 32.5°C

Operating temperature range

50 to 90.5°F

Orderable supplies

HP LaserJet Toner Collection Unit 3WT90A, HP LaserJet 110V Fuser Kit 3WT87A, HP LaserJet 220V Fuser Kit 3WT88A, HP LaserJet Image Transfer Belt Kit 3WT89A

Output capacity

Up to 250 sheets

Package dimensions (W x D x H)

30.95 x 28.98 x 21.98 in

Package dimensions (W x D x H)

786 x 736 x 558 mm

Package weight

116.6 lb

Package weight

52.9 kg

Page yield footnote number

[7]

Pallet dimensions

31.1 x 29.92 x 92.9 in

Pallet dimensions (W x D x H)

790 x 760 x 2359 mm

Pallet weight

221.5 kg

Pallet weight

488.4 lb

Paper handling input, optional

Add up to two: 1x550-sheet paper tray; Add up to one: 2x550-sheet paper tray and stand, 2,700 (1,600+1,100) sheet high capacity input paper tray and stand, or Cabinet stand

Paper handling input, standard

100-sheet multipurpose tray, 550-sheet input tray

Paper handling output, standard

250-sheet output bin

Paper trays, maximum

6

Paper trays, standard

2

Plug and play

HP Smart Install

Power

Input voltage: 100 V to 127 V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 12 A; Input voltage: 220 V to 240 V nominal (+/-10%), 50 - 60 Hz nominal (+/- 3 Hz), 6 A

Power consumption

870 watts (max. printing), 850 watts (typical printing) 48 watts (Ready), 0.6 watts (Sleep), 0.6 watts (HP Auto-Off/Auto On), 0.08 watts (Auto-Off), 0.08 watts (Off)

Power consumption footnote number

[4]

Power supply type

Built-in 115V or 220V Power Supply

Print colors

Yes

Print languages

HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint™

Print quality black (best)

Up to 1200 x 1200 dpi

Print quality black (normal)

Up to 600 x 600 dpi

Print quality color (best)

Up to 1200 x 1200 dpi

Print resolution black (fine lines)

Up to 1200 x 1200 dpi

Print resolution color (fine lines)

Up to 1200 x 1200 dpi

Print resolution color (normal)

Up to 600 x 600 dpi

Print Resolution Technologies

HP ImageREt 4800, Enhanced (600x600 dpi), Fine Lines (1200x1200 dpi), Quickview (300x300 dpi)

Print speed

Print speed up to 40 ppm (black) and 40 ppm (color)

Print speed (A3/tabloid) footnote number

[16]

Print speed (A4/letter) footnote number

[13]

Print speed black (ISO, A4)

Up to 41 ppm

Print speed black (ISO, letter)

Up to 40 ppm

Print speed black (Landscape, A5)

Up to 35 ppm

Print speed black (normal, A3)

Up to 26 ppm

Print speed black (normal, tabloid)

Up to 26 ppm

Print speed color (ISO)

Up to 40 ppm

Print Speed Color (ISO)

Up to 41 ppm

Print speed color (Landscape, A5)

Up to 35 ppm

Print speed color (normal, A3)

Up to 26 ppm

Print speed color (normal, tabloid)

Up to 26 ppm

Print speed duplex (A3)

Up to 18 ipm

Print speed duplex (A3)

Up to 18 ipm

Print speed duplex (A4)

Up to 41 ipm

Print speed duplex (A4)

Up to 41 ipm

Print speed duplex (letter)

Up to 40 ipm

Print speed duplex (letter)

Up to 40 ipm

Print speed duplex (tabloid)

Up to 18 ipm

Print speed duplex (tabloid)

Up to 18 ipm

Print speed footnote (A5)

[15]

Print technology

Laser

Print Technology

Laser

Printer Management

HP Printer Assistant; HP Utility (Mac); HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)

Printer smart software features

Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB

Processor speed

1.2 GHz

Product note

FCC Class A emissions device for use in commercial environments, not residential environments[3]

Quantity per pallet

4

Recommended media weight (duplex)

16 to 43 lb

Recommended media weight (duplex)

60 to 163 g/m²

Recommended monthly page volume

Up to 40,000

Recommended monthly page volume footnote number

[10]

Recommended operating humidity range

30 to 70% RH

Recommended operating temperature range

15 to 27°C

Recommended operating temperature range

59 to 80.6°F

Replacement cartridges

HP 658A Black LaserJet Toner Cartridge (~7,000 pages); HP 658A Cyan LaserJet Toner Cartridge (~6,000 pages); HP 658A Magenta LaserJet Toner Cartridge (~6,000 pages); HP 658A Yellow LaserJet Toner Cartridge (~6,000 pages); HP 658X Black LaserJet Toner Cartridge (~33,000 pages); HP 658X Cyan LaserJet Toner Cartridge (~28,000 pages); HP 658X Magenta LaserJet Toner Cartridge (~28,000 pages); HP 658X Yellow LaserJet Toner Cartridge (~28,000 pages); HP 660A Original LaserJet Imaging Drum (~65,000 pages, universal for all 4 colors)

Replacement cartridges footnote number

[6]

Right margin (A4)

5 mm

RMN number

BOISB-1813-00

Safety

IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010; Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.

Security management

Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in

Services (Care Pack)

UB5C3E - HP 3y NBD w/DMR CLJ M751 SVC; UB5C4E - HP 4y NBD w/DMR CLJ M751 SVC; UB5C5E - HP 5y NBD w/DMR CLJ M751 SVC; UB5C6E - HP 3y 4h 9x5 w/DMR CLJ M751 SVC; UB5C7E - HP 4y 4h 9x5 w/DMR CLJ M751 SVC; UB5C8E - HP 5y 4h 9x5 w/DMR CLJ M751 SVC; UB5C9E - HP 3y ChnlPartsOnly CLJ M751 SVC; UB5D0E - HP 4y ChnlPartsOnly CLJ M751 SVC; UB5D1E - HP 5y ChnlPartsOnly CLJ M751 SVC; UB5D2PE - HP 1y PW NBD w/DMR CLJ M751 SVC; UB6X3PE - HP 2y PW NBD w/DMR CLJ M751 SVC; UB6X4PE - HP 1y PW w/DMR 4h 9x5 CLJ M751 SVC; UB6X5PE - HP 2y PW w/DMR 4h 9x5 CLJ M751 SVC; UB6X6PE - HP 1y PW ChnlPartsOnly CLJ M751 SVC; UB6X7PE - HP 2y PW ChnlPartsOnly CLJ M751 SVC

Software included

No software solutions are included in the Box, only on <http://hp.com>, <http://123.hp.com>;

Standard input capacity (envelopes)

Up to 10

Standard media sizes (duplex)

A3; A4; A4-R; A5; 8K; 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); B4 (JIS); B5 (JIS); Oficio; RA3; RA4; SRA3; SRA4

Standard media sizes (duplex, imperial)

Letter; Executive; Tabloid; Ledger; Oficio (8.5 x 13 in)

Standard output capacity (envelopes)

Up to 50 envelopes

Standard output capacity (transparencies)

Up to 150 sheets

Storage device and direct print support

USB printing; Right-side facing USB/Flash drive

Storage temperature range

-20 to 40°C

Storage temperature range

-4 to 104°F

Supplies feature

HP JetIntelligence Cartridge

SureSupply footnote number

[17]

SureSupply supported

Yes

Target user and print volume

For teams up to 20 users; Prints up to 40,000 pages/month

Tariff numbers

8443321000 (EU Base HTS); 8443321010 (AM Base HTS); 84433231 (AP Base HTS)

Tech spec footnote

[1] Standard cartridges included; yields 7,000 black and 6,000 color composite (C/M/Y) pages. Drums included; yields 65,000 black and color pages.

Tech spec footnote

[10] HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Tech spec footnote

[11] Solution software available on 123.hp.com

Tech spec footnote

[12] EPEAT® registered where applicable. EPEAT registration varies by country. See <http://www.epeat.net> for registration status by country.

Tech spec footnote

[13] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[14] Measured using ISO/IEC 17629. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[15] Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type.

Tech spec footnote

[16] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[17] Measured using ISO/IEC 17629. For more information see <http://www.hp.com/go/printerclaims>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[18] Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type.

Tech spec footnote

[2] Without paper trays extended.

Tech spec footnote

[3] With print cartridges.

Tech spec footnote

[4] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.

Tech spec footnote

[5] Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled.

Tech spec footnote

[6] Average black declared yields based on ISO/IEC 19752 and continuous printing. Average color composite (C/M/Y) declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see <http://www.hp.com/go/learnaboutsupplies>.

Tech spec footnote

[7] Acoustic values are subject to change. For current information see <http://www.hp.com/support>. Configuration tested: base model, simplex printing, A4 paper at an average of 41 ppm.

Tech spec footnote

[8] To achieve maximum memory, purchase a DIMM accessory (TAA compliant only with TAA compliant DIMM). A firmware update may be required for configuration page to accurately reflect the accessory DIMM is installed.

Tech spec footnote

[9] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Technology logo, print 1

Publication logos/AMS_EnergyStar.jpg

Technology logo, print 2

Publication logos/AMS_windows_10.jpg

Technology logo, print 3

Publication logos/AMS_mac_hires.jpg

Technology logo, print 4

Publication logos/AMS_AirPrint.jpg

Technology logo, print 5

Publication logos/AMS_Mopria.jpg

Technology logo, print 6

Publication logos/AMS_hp_eprint.jpg

Top key features

Front-facing USB printing; Roam; Two-sided printing

Top margin (A4)

5 mm

Tray capacity

650

Typical electricity consumption (TEC) footnote

BA TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.

Typical electricity consumption (TEC) footnote number

[5]

Typical electricity consumption (TEC) number

1.93 kWh/Week (Blue Angel); 0.551 kWh/Week (Energy Star 3.0)

UNSPSC code

43212105

UPC number

(AB0) 192018847736; (AB2) 192018847743; (ABJ) 192018847750; (ABT) 192018847798; (ABY) 192018847804; (AC4) 192018847859; (AC8) 192018847866; (ACJ) 192018847767; (ACQ) 192018847811; (AKV) 192018847873; (B13) 192018847828; (B19) 192018847835; (BAZ) 192018847842; (BBU) 192018847774; (BGJ) 192018847903; (BGM) 192018847781

Warm-up time

131 sec

Warranty

One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award

winning service and support options in your region. (Warranty Code 4G; Warranty ID A001)

Web address for additional information

Solutions: <http://www.hp.com/go/gsc>; Fonts and IPDS Emulation: <http://www.hp.com/go/laserjetfonts>; HP Web Jetadmin: <http://www.hp.com/go/wja>; HP Universal Print Driver: <http://www.hp.com/go/upd>; HP JetAdvantage Security Manager: <http://www.hp.com/go/securitymanager>; HP JetAdvantage On Demand Cloud Solutions: <http://www.hp.com/go/JetAdvantageondemand>

Weight

45.1 kg

Weight

99.4 lb

Weight (imperial) footnote number

[3]

Weight (metric) footnote number

[3]

Weight note (imperial)

With print cartridges

Weight note (metric)

With print cartridges

What is in the box footnote number

[1,6]

What's in the box

HP Color LaserJet Enterprise M751n printer; Four preinstalled HP LaserJet toner cartridges; Four preinstalled HP Original LaserJet Imaging Drums (~65,000 pages each color); Guide (Getting started Guide); Power cord[1,6]

Wireless capability

Optional, enabled with purchase of a wireless hardware accessory: HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A, (Dual band Wireless Station and Wi-Fi Direct functionality); HP Jetdirect 2900nw Print Server J8031A (Dual band Wireless Station)

© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.