

HP LaserJet Enterprise M608n (K0Q17A)

Active as of 5/1/2017

Detailed Specifications

Accessories

2MU47A HP Accessibility Assistant; 2NR03A HP 1 GB 90-pin DDR3 DIMM; 2NR12A HP Removable Hard Drive Enclosure; 3JN69A HP Jetdirect 3100w BLE/NFC/Wireless Accessory; 5EL03A HP TAA Version Secure Hard Disk Drive; B5L28A HP Internal USB Ports; B5L29A HP High-Performance Secure Hard Disk; CC543B HP SmartCard NIPRNet Solution for US Government; F5S62A HP Trusted Platform Module Accessory; G6W84A HP 1 GB 90-pin DDR3 DIMM; HG271TT HP Barcode Printing Solution – USB; HG277TT HP MICR Printing Solution – USB; HG281TS HP Barcodes and More Printing Solution for USB version 2 slot based LaserJet; HG282TT HP Scalable Barcodes Printing Solution for USB version 2 slot based LaserJet; J8030A HP Jetdirect 3000w NFC/Wireless Accessory; J8031A HP Jetdirect 2900nw Print Server; J8J96A HP Staple Cartridge Refill; L0H17A HP LaserJet 550-sheet Paper Tray; L0H18A HP LaserJet 2100 Sheet Paper Tray; L0H19A HP LaserJet Printer Stand; L0H20A HP LaserJet Stapler/Stacker/Mailbox; L0H21A HP LaserJet Envelope Feeder; L0H22A HP LaserJet Extension Tray Cover

Acoustic power emissions (active, printing)

6.9 B(A)

Acoustic power emissions (ready)

Inaudible

Acoustic power note

Acoustic values are subject to change. For current information see http://www.hp.com/support. Noise measured during printing mono simplex A4 at 62ppm.

Acoustic pressure emissions bystander (active, printing)

55 dB(A)

Acoustic pressure emissions bystander (ready)

Inaudible

Automatic paper sensor

No

Best technical electricity consumption (TEC)

2.684 kWh/week

Best technical electricity consumption (TEC) footnote number

[13]

Blue Angel (sleep mode)

3.21 watts

Blue Angel compliant

No, please refer to the ECI (Ecolabel Comparison Information) document

Bottom margin (A4)

4.3 mm

Cable included

No, please purchase (USB) cable separately

Capacity

Optional 500 GB Hard Disk

Code name

Titanium 65

Compatible Network Operating Systems

Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2008/2008R2/2008 R2 SP1, Citrix

on Windows Server 2012/2012R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3) for Windows Server 2008 Terminal Services 32- and 64-bit, Citrix XenApp 6.0/6.5 [for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenApp 6.0/6.5/7.5 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenApp 7.5 [for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit], Citrix XenDesktop 5.6 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenDesktop 5.6/7.0/7.5 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenDesktop 7.0/7.5 [for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit], Novell NetWare 6.5/SP8 Novell Clients www.novell.com/iprint, Novell iPrint Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Novell Servers www.novell.com/iprint), Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services)

Compatible Operating Systems

Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 Yosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets)

Connectivity, optional

HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w NFC/Wireless Accessory J8030A

Connectivity, standard

1 Hi-Speed Device USB 2.0; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket

Control panel

2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad

Count of cartons per pallet layer

4

Count of layers in pallet

4

Country of origin

Made in China (ABO, AB2, ABJ, ACJ, BBU, BGM, ACQ, ABT, ABY, B13, B19, BAZ, BGJ)

Datasheet photo 1

Publication photos/K0Q17A.jpg

Datasheet photo 4

Publication photos/m608 walkaround.jpg

Datasheet publication number

4AA6-9784

Display

2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle)

Display area (imperial)

2.125 x 1.59 in

Display area (metric)

54 x 40.5 mm

Downloadable software

HP Easy Start (Guided Software Install for Windows OS and Mac); HP ePrint Software (ePrint Mobile Driver for Windows); HP ePrint Software (for Windows); HP Imaging & Printing Security Center; HP JetAdvantage Security Manager; HP Mobile Printing http://www8.hp.com/us/en/ads/mobility/overview.html; HP PCL6 (XPS) print driver only (No installer for "Add Printer" installs); HP PCL6 (XPS) print driver with installer; Product Documentation and Support; HP Proxy Agent Software; HP Universal Print Drivers (PCL6 & PS for Windows); Linux/Unix Print Drivers; Mac Software Solution; Printer Administrator Resource Kit; SAP (PS Print Drivers); Web JetAdmin; Windows driver only solution; Windows Full Software Solution

Driver updates

Current HP printer drivers and software can be obtained from the HP Customer Care Web site: In the US, go to

www.hp.com/support/colorljM608; Outside the US, go to http://www.hp.com/support 1. Go to http://www.hp.com/support. Select the country/region. 2. Select Drivers & Downloads 3. Enter a product name/number. 4. Under Download Options, select Drivers, Software & Firmware 5. Select the operating system version. 6. Then select DOWNLOAD.

Duplex printing

Manual (driver support provided)

Duty cycle (monthly, A4)

Up to 275,000 pages

Duty cycle (monthly, letter)

Up to 275,000 pages

Duty cycle note

Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Electromagnetic compatibility

CISPR 22:2008 (International) - Class A, EN 55022: 2010 (EU) - Class A, EN 61000-3-2: 2006 +A1: 2009 +A2: 2009, EN 61000-3-3: 2008, EN 55024: 2010, EMC Directive 2004/108/EC, FCC CFR 47 Part 15 Class A / ICES-003, Issue 5 Class A, Other EMC approvals as required by individual countries

Energy savings feature technology

HP Auto-On/Auto-Off Technology; Instant-on Technology

Energy star certified

No

Envelope Feeder

Yes, 75 (optional)

Environmental

Mercury-free

FCC Class A emissions

FCC Class A emissions - for use in commercial environments, not residential environments

Finished output handling

Sheetfed

First page out black (A4, ready)

As fast as 5.4 sec

First page out black (A4, sleep)

As fast as 7.9 sec

First page out black (letter, ready)

As fast as 5.3 sec

First page out black (letter, sleep)

As fast as 7.8 sec

First page out footnote number

[9]

Fonts and typefaces

105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserjetfonts

Functions

Print

Image legal disclaimer

Product image may differ from actual product

Input capacity

Up to 650 sheets

Internal Storage

Optional, 500 GB (with accessory B5L29A)

Left margin (A4)

Legal disclaimer

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

Mac compatible

Yes

Maximum dimensions (W x D x H)

17 x 40.9 x 17.8 in

Maximum dimensions (W x D x H)

431 x 1040 x 453 mm

Maximum input capacity (sheets)

Up to 4400 sheets

Maximum Memory

1.5 GB, MAX memory, when 1GB Accessory DIMM is installed

Maximum metric depth

1040

Maximum metric height

453

Maximum metric width

431

Maximum output capacity (sheets)

Up to 1300 sheets

Media sizes supported

feeder 1: A4, A5, A6, RA4, B5 (JIS), B6 (JIS), 10 x 15 cm, Oficio (216 x 340 mm), 16K, envelopes (C5, B5, C6, DL ISO), Postcard (JIS single and double); feeder 2: A4, A5, A5-R, B5 (JIS), 16K

Media sizes supported

feeder 1: Letter, legal, statement, executive, Oficio $(8.5 \times 13 \text{ in})$, envelopes [No. 9, No. 10, Monarch(7 3/4)], 3 \times 5, 4 \times 6, 5 \times 7, 5 \times 8; feeder 2: letter, executive, legal

Media sizes, custom

feeder 1: 3 x 5 to 8.5 x 14 in; feeder 2: 3.90 x 5.83 to 8.5 x 14 in

Media sizes, custom

feeder 1: 76 x 127 to 216 x 356 mm; feeder 2: 99 x 148 to 216 x 356 mm

Media types

Paper (plain, light, bond, recycled, heavy, extra heavy, cardstock, pre-printed, pre-punched, colored, rough, heavy rough), mono transparency, labels, letterhead, envelope, heavy envelope

Media weight (tray 1)

60 to 200 g/m²

Media weight, supported

Feeder 1: 16 to 53 lb bond (plain), 16 to 24 lb (envelopes); feeder 2: 16 to 32 lb bond (plain)

Media weight, supported

Feeder 1: 60 to 199 g/m²; feeder 2: 60 to 120 g/m²

Memory

512 MB

Memory footnote

[12]

Memory Slots

1 slot, 90-pin

Memory upgrade

Expandable to 1.5 GB through 1 GB 90-pin DDR3 DIMM

Metric depth

466

Metric height

380

Metric width

431

Minimum dimensions (W x D x H)

17 x 18.3 x 15 in

Minimum dimensions (W x D x H)

431 x 466 x 380 mm

Minimum System Requirements

2 GB available hard disk space; OS hardware requirements see microsoft.com

Minimum System Requirements for Macintosh

1.3 GB available hard drive space; Internet; OS hardware requirements see Apple.com for more info

Mobile printing capability

HP ePrint; Apple AirPrint™; Mopria-certified

Mobile printing capability footnote number

[6]

Network capabilities

Yes, via HP Jetdirect Ethernet embedded print server (standard) which supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11a/b/g/n wireless networking (optional).

Network protocols, supported

Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint, FTP Print, Google Cloud Print; DISCOVERY: SLP, Bonjour, Web Services Discovery; IP CONFIG: IPv4 (BootP, DHCP, AutoIP, Manual, TFTP Config, ARP-Ping), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPs, Telnet, TFTP Config, FTP FW Download, Syslog; Security: SNMPv3, SSL Cert Management, Firewall, ACL, 802.1x

Non-Operating Humidity Range

10 to 80% RH

Number of print cartridges

1 (black)

Number of users

10-30 Users

Operating humidity range

10 to 80% RH

Operating system (supported note)

Full solution software available only for Windows 7 and newer, UPD software available only for Windows 7 and newer, HP Software for Mac and Windows is no longer included on the CD, but can be downloaded from 123.hp.com, Legacy Windows Operating Systems (XP, Vista, and equivalent servers) get print and Scan drivers only with a reduced feature set, Windows RT OS for Tablets (32-&64-bit) uses a simplified HP print driver built into the RT OS

Operating temperature range

10 to 32.5℃

Operating temperature range

50 to 90.5°F

Orderable product number

KOQ17A#ABO, KOQ17A#AB2, KOQ17A#ABJ, KOQ17A#ACJ, KOQ17A#BBU, KOQ17A#BGM, KOQ17A#ABT, KOQ17A#ABY, KOQ17A#ACQ, KOQ17A#B13, KOQ17A#B19, KOQ17A#BAZ, KOQ17A#BGJ

Orderable supplies

HP Staple Cartridge Refill J8J96A, HP LaserJet 110 v Maintenance Kit L0H24A, HP LaserJet 220 v Maintenance Kit L0H25A

Output capacity

Up to 500 sheets

Package dimensions (W x D x H)

23.50 x 19.57 x 21.22 in

Package dimensions (W x D x H)

597 x 497 x 539 mm

Package weight

27.2 kg

Package weight

60.1 lb

Page yield footnote number

[11]

Pallet dimensions

47.24 x 39.37 x 90.94 in (AP), 47.24 x 39.37 x 91.33 in (EMEA & AMS)

Pallet dimensions (W x D x H)

1200 x 1000 x 2310 mm (AP), 1200 x 1000 x 2320 mm (EMEA & AMS)

Pallet weight

433.59 kg (NA, EMEA, AP)

Pallet weight

955.89 lb (NA, EMEA, AP)

Paper handling input, optional

Optional 1x550-sheet paper feeder, optional 1x550 paper feeder and stand with cabinet, optional 3x550-sheet paper feeder and stand, optional high-capacity paper feeder and stand with 1x550 sheet feeder and 1x2,000-sheet feeder

Paper handling input, standard

100-sheet multipurpose feeder, 550-sheet input feeder

Paper handling output, optional

Optional 5 bin stapler stacker

Paper handling output, standard

500 sheet output bin

Paper trays, maximum

Up to 6

Paper trays, standard

2

Post warranty repair & maintenance

http://www.hp.com/support

Power

100V - 127V nominal @ +/-10% (min 90V, max 140V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 12 A; 220V - 240V nominal, @ +/-10% (min 198V, Max 264V); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 6 A

Power consumption

780 watts (printing), 15.3 watts (ready), 3.1 watts (sleep), < 0.1 watts (Auto Off/Manual On), < 0.1 watts (Manual Off)

Power consumption footnote number

[3]

Power supply type

Built in 115V or 220V Power Supply (Not dual voltage, power supply varies by part number with # Option code identifier)

Print colors

Nο

Print languages

HP PCL 6, HP PCL 5 (HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrintTM

Print quality black (best)

Up to 1200 x 1200 dpi

Print quality black (normal)

FastRes 1200

Print resolution black (fine lines)

Up to 1200 x 1200 dpi

Print Resolution Technologies

FastRes 1200; 1200 x 1200 dpi

Print speed (A4/letter) footnote number

[7]

Print speed black (ISO, A4)

Up to 61 ppm

Print speed black (ISO, letter)

Up to 65 ppm

Print speed black (Landscape, A5)

Up to 100 ppm

Print speed black (Portrait, A5)

Up to 6 ppm

Print speed footnote number (A5)

[8]

Print technology

Laser

Print Technology

Laser

Printer Management

HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver

Printer smart software features

Print preview, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB

Processor speed

1.2 GHz

Product note

FCC Class A emissions device for use in commercial environments, not residential environments[8]

Quantity per pallet

16

Recommended monthly page volume

5000 to 25000

Recommended monthly page volume note

HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Recommended operating humidity range

30 to 70% RH

Recommended operating temperature range

15 to 27℃

Recommended operating temperature range

59 to 80.6ºF

Replacement cartridges

HP 37A Black Original LaserJet Toner Cartridge (11,000 yield) CF237A; HP 37X High Yield Black Original LaserJet Toner Cartridge (25,000 yield) CF237X; HP 37Y Extra High Yield Black Original LaserJet Toner Cartridge (41,000 yield) CF237Y

Replacement cartridges footnote number

[5]

Right margin (A4)

RMN number

BOISB-1502-00

Safety

IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2007 / IEC 60825-1:2007 (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010; Low Voltage Directive 2006/95/EC with CE Mark Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007. Other safety approvals as required by individual countries

Security management

Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key; and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs, ...); Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessable in Arcsight and Splunk SIEMs

Service & support options

Free telephone support for basic setup, installation, and troubleshooting in North America, Europe, and Asia Pacific during warranty; Optional HP Supportpack for 4-hour response during standard business hours; Optional HP Supportpack for 24 hours a day, 7 days a week; Optional HP Supportpack for Comprehensive Technical Support

Service level options

Assembly, network configuration, and basic administrator familiarization

Service level options

Onsite replacement of your printer's maintenance kit including parts, materials, and labor

Service level options

Onsite service the next business day after the service call is received

Service level options

Onsite support within four hours after the service call is received within the coverage window

Service level options, header

4 hour Onsite Support

Service level options, header

Installation with Network Configuration Service

Service level options, header

Maintenance Kit Replacement Service

Service level options, header

Next Business Day Onsite Support

Services

Customers can retain their hard disk drive and keep control of sensitive data.

Services

Sends an HP technician to customers' site the same business day for repair, within 4 hours, if the issue cannot be resolved through remote support. Various support window times are available, for different requirements.

Services

Ships a permanent replacement unit overnight via premium airfreight, if hardware issue cannot be resolved remotely. Shipping charges are prepaid by HP.

Services (Care Pack)

U9NE2E - HP 5 year Next Business Day HW Support w/Defective Media Retention; U9NE5E - HP 5 year 4 hour 9x5 HW Support w/Defective Media Retention; U9NE8E - HP 5 year 4 hour 13x5 HW Support w/Defective Media Retention; U9NF1E - HP 5 year Next Business Day Call To Repair HW Support w/DMR; U9NF4E - HP 5 year Next Business Day Exchange Service; U9NG5PE - HP 2 year Post Warranty Next Business Day Hardware Support w/DMR; U9NG7PE - HP 2 year Post Warranty 4 hour 9x5 Hardware Support w/DMR; U9NG8PE - HP 1 year Post Warranty 4 hour 13x5 Hardware Support w/DMR; U9NH0PE - HP 2 yr Post Warranty Next

Business Day Call To Repair HW Support w/DMR; U9NH1PE - HP 1 year Post Warranty Next Business Day Exchange Service

Services description headline 01

Next Business Day Onsite with Defective Media Retention:

Services description headline 02

Next Business Day Exchange:

Services description headline 03

Same Day Onsite – 4 hour 9x5 and 13x5:

Software included

HP Connected, HP Device Experience (DXP), HP PCL 6 (XPS) Printer Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to 123.HP.com or OS App Source for printer software), Online user manuals

Standard input capacity (envelopes)

Up to 10

Standard output capacity (envelopes)

Up to 75 envelopes

Standard output capacity (transparencies)

200

Storage footnote number

[10]

Storage temperature range

-20 to 40°C

Storage temperature range

-4 to 104ºF

Sub-brand name

LaserJet

SureSupply note

HP SureSupply alerts you when you should replace a print cartridge and helps you purchase locally or via the Internet. For more information, visit http://www.hp.com/learn/suresupply. Only available with original HP supplies; Internet access required.

SureSupply supported

Yes

Target user and print volume

For teams over 25 users; Prints up to 25,000 pages/month

Tariff numbers

8443321010 (AM); 8443321090 (EU); 84433230 (AP)

Tech spec footnote

[1] EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.

Tech spec footnote

[10] eMMC is non-volatile storage; Firmware encryption (AES 128 or AES 256) of customer/job data; Secure Cryptographic Erase – Job Data; Secure Erase – Disk

Tech spec footnote

[11] Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit http://www.hp.com/go/learnaboutsupplies

Tech spec footnote

[12] 1 GB "Slim DIMM" G6W84A

Tech spec footnote

[13] Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled.

Tech spec footnote

[2] Cartridges included; yields 11,000 black pages based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see

http://www.hp.com/go/learnaboutsupplies

Tech spec footnote

[3] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

Tech spec footnote

[4] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.

Tech spec footnote

[5] Average color composite (C/M/Y) and black declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies.

Tech spec footnote

[6] May require a firmware upgrade to be compatible, download at http://www.hp.com/go/support

Tech spec footnote

[7] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[8] Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type.

Tech spec footnote

[9] Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Technical support information

http://www.hp.com/support/ljM608

Technology logo, print 1

Publication logos/AMS_windows_10.jpg

Technology logo, print 2

Publication logos/AMS_mac_hires.jpg

Technology logo, print 3

Publication logos/AMS_Mopria.jpg

Technology logo, print 4

Publication logos/AMS_hp_eprint.jpg

Technology logo, print 5

Publication logos/AMS_AirPrint.jpg

Technology logo, print 6

Publication logos/AMS_USB_hi speed.jpg

Top margin (A4)

4.3 mm

Total package service recommended services description

4 hour Onsite Support, Maintenance Kit Replacement Service or Preventive Maintenance, Installation with Network Configuration Service

Total package service recommended services description

Next Business Day Onsite Support

Total package service recommended services description

Next Business Day Onsite Support, Maintenance Kit Replacement Service or Preventive Maintenance Service, Installation with Network Configuration Service

Total package service recommended services description headline

Basic Care (minimum recommended support)

Total package service recommended services description headline

Optimized Care (optimum performance and stability)

Total package service recommended services description headline

Standard Care (high level of uptime)

Total package service recommended services preface

Downtime can have serious consequences, so HP provides support recommendations beyond the standard warranty. You benefit from reduced risk, maximized uptime, and predictable service delivery while avoiding unbudgeted repair costs. Choose from:

Total package service related services note

For more information about HP Care Pack, HP Contractual, or HP Managed Print Services, visit http://www.hp.com/go/printservices.

Tray capacity

650

Typical electricity consumption (TEC) footnote number

[4]

Typical electricity consumption (TEC) number

ES: 2.622 kWh/week, BA: 2.425 kWh/week

UNSPSC code

43212105

UPC number

889894068347

Warm-up time

130 sec

Warranty

One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region. (wty code 4G)

Web address for additional information

Solutions: http://www.hp.com/go/gsc; Fonts and IPDS Emulation: http://www.hp.com/go/laserjetfonts; HP Web Jetadmin: http://www.hp.com/go/wja; HP Universal Print Driver: http://www.hp.com/go/upd; HP JetAdvantage Security Manager: www.hp.com/go/securitymanager; HP JetAdvantage On Demand Cloud Solutions: www.hp.com/go/JetAdvantageondemand

Weight

21.6 kg

Weight

47.7 lbs

Weight note (imperial)

With print cartridges

Weight note (metric)

With print cartridges

What is in the box footnote number

[2]

What's in the box

HP LaserJet Printer; HP Black Original LaserJet Toner Cartridge (~11K yield); CD with software drivers and documentation; Documentation (Hardware Install Guide); Power cord

Wireless capability

Optional, enabled with purchase of HP Jetdirect 2900nw Print Server J8031A or HP Jetdirect 3000w NFC/Wireless Accessory J8030A

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.